

Motor Specifications

Motor Kv	5800KV
Max Lipo Cell	2s-3s (12.6 MAX INPUT VOLT)
Stator Diameter	11 mm
Stator Length	15 mm
No. of Stator Arms	9
No. Magnet Poles	6
Single Wire Diam.	0.23 mm
Max Continuous Current	12A
Max Continuous Power	150W
Weight	12.2g
Outside Diameter	13.8 mm
Body Length	22.3 mm
Shaft Diameter	2 mm
Pinion Shaft Diameter	1.5 mm
Overall Shaft Length	30.1 mm
Motor Timing	5deg
Drive Frequency	8kHz

Lynx EOX 1102 - 2-3S - 8350 KV motor is the ultimate powerhouse for your 130X. Specifically design for 3S configuration.

The high quality of all components and material used, as the choice of a special single wire rewind system grade this motor as a Limit Edition.

Be careful to handle Lynx EOX Motor to avoid personal injury, and install the motor following the quick instruction available on Lynx web site.

For any extra information please contact us by service ticket at WWW.LYNXHLLI.COM

IMPORTANT USER INFORMATION:

We REMIND that Lynx EOX 1102 - 2-3S 5800 KV CANNOT used with 4S LiPo configuration, MAX Input Voltage is 12.6V, 3S LIPO.

Extra Voltage can damage the Motor.